


## MCW09

### MCW09 "PROFESSIONAL" SINGLE SECURITY CRANE SCALE SERIES



Stainless steel digital crane scale with IP67 protection against dust and sprays, 40mm DOT LED large display, for maximum visibility from all angles and in any lighting condition, even direct sunlight.

**The single security system makes them suitable for lifting and weighing the load.**

Sturdy and reliable, usable indoors as well as outdoors. Minimum reduction of the crane's lifting space.

The models with up to 15000 kg capacity are fitted with test certificate obtained with sample weights, for higher capacities the certificate is available on request.

Working in cooperation with:

**E H OAKLEY LIMITED**

Ladymead Farm Unit 4 - HP22 4AN - Aylesbury, Bucks - UNITED KINGDOM  
Tel. 0044 (0) 1296 393133 Fax. 0044 (0) 1296 397070  
adrian@oakleyweigh.co.uk

**The best solution  
for advanced industrial  
applications**

## CRANE SCALE: MAIN FEATURES

- Single security system, for the lifting and the weighing of the load.
- In compliance with the directives 2006/42 CE, UNI EN 13155/2009, UNI EN 13889, 2014/30/EU.
- Extremely bright large red DOT LED 40mm display, which guarantees a perfect visibility of the weight from any angle, also from a long distance with direct sunlight.  
Usable indoors as well as outdoors, great visibility also in full sunlight.
- Adjustable brightness intensity.
- Sturdy STAINLESS steel structure, with IP67 protection degree of the load cell and the electronics, against dust and sprays.
- Fitted with approved galvanised shackles:
  - GR6 for MCW09T3
  - GR6 for MCW09T6
  - GR9 for MCW09T9
  - GR12 for MCW09T12
  - GR17 for MCW09T17
  - GR25 for MCW09T25
  - GR35 for MCW09T30
  - GR55 for MCW09T50
- Extremely reduced distance between upper and lower shackles.
- Precision: +/- 0,05% on F.S. for 3T to 9T models
- Precision: +/- 0,1% on F.S. for 12T to 50T models
- 5-key waterproof keypad: ZERO, AUTOMATIC TARE, MODE, PRINT, and ON/OFF.
- Programmable digital filter, for an excellent weight display in any working condition.
- Programmable automatic switch-off function, either through keypad or remote control.
- Fitted with radiofrequency 6-key remote control, configurable as simple automatic tare or as a remote keypad.
- Configured for an 2,4 GHz radio interface or WiFi, for connection to PC or to a remote terminal and printer.
- Rechargeable battery, with an average life of about 30 hours.
- Configured for a second optional extractable battery for 24/7 continuous use.
- Fitted with 230Vac 50 Hz battery charger. EU, UK, US, AU plugs included as standard.
- Programmable digital calibration and Set-Up directly from the keypad or from PC through Dinitools.
- Operating temperature range: -10/+40 °C.

### PACKAGING IS INCLUDED IN THE PRICE

for the complete protection against scratches and bumps during transportation. The crane scale is shipped inside a sturdy wooden case which is custom made (MCW09T12-1, MCW09T17-1, MCW09T25-1, MCW09T30-1, MCW09T50-1 versions).

## CRANE SCALE: REMOTE CONTROL FUNCTIONS

- The crane scale is fitted with a radiofrequency remote control which allows to do the Zeroing; the tare; enable / disable functions; printing; switching-off the crane scale.

## CRANE SCALE: SELECTABLE FUNCTIONS

- PEAK (maximum value read).
- HOLD (lock of the displayed weight).
- Weighing totalization.
- lb/kg/N conversion (see DFW weight indicators for more functions).
- +/- checkweighing.
- Percentage weighing.
- Counting.
- Peer-to-peer.
- High Resolution Weighing x 10.

## CRANE SCALE: OPTIONS (ONLY AT TIME OF ORDER)

- Radio frequency weight transmission to remote indicator, up to 45m indoors.
- 2.4 GHz radio interface.
- Wi-Fi interface.
- Remote weight indicator connected in radio frequency, with the printer or other accessories.
- ACCREDIA calibration certificate according to OIML/ASTM standards.

### DETAIL 1



Crane scale MCW09: side view

### DETAIL 2



Crane scale MCW09: extractable battery view

### DETAIL 3



Crane scale MCW09: extra-bright 40mm display

### DETAIL 4

| CODE     | WEIGHT (kg)       |                |
|----------|-------------------|----------------|
|          | WITHOUT PACKAGING | WITH PACKAGING |
| MCW09T3  | 16                | 17             |
| MCW09T6  | 17                | 18             |
| MCW09T9  | 21                | 22             |
| MCW09T12 | 26                | 55             |
| MCW09T17 | 36                | 74             |
| MCW09T25 | 55                | 79             |
| MCW09T30 | 70                | 108            |
| MCW09T50 | 137               | 161            |

### VERSIONS

#### Available versions

| Codice     | Max (kg) | d (kg) | <b>M</b> (kg) | d HR (kg)* |
|------------|----------|--------|---------------|------------|
| MCW09T3-1  | 3000     | 1      | 1             | 0,5        |
| MCW09T6-1  | 6000     | 2      | 2             | 1          |
| MCW09T9-1  | 9000     | 5      | 5             | 2          |
| MCW09T12-1 | 12000    | 5      | -             | 2          |
| MCW09T17-1 | 17000    | 10     | -             | 5          |
| MCW09T25-1 | 25000    | 10     | -             | 5          |
| MCW09T30-1 | 30000    | 20     | -             | 10         |
| MCW09T50-1 | 50000    | 20     | -             | 10         |

(\* ) The HR division is obtainable only with the relative EHR option



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano - Modena - Italy  
Tel. +39.0536 843418

***E H OAKLEY LIMITED***

*Ladymead Farm Unit 4 - HP22 4AN - Aylesbury, Bucks - UNITED KINGDOM*

*Tel. 0044 (0) 1296 393133 Fax. 0044 (0) 1296 397070*

*adrian@oakleyweigh.co.uk*

**SALES AND TECHNICAL ASSISTANCE SERVICE**

*All the specifications and images can be subject to variations and upgrades without prior notice.*