

## TPWLKI

### TPWLKI "LOGISTIC" SERIES STAINLESS STEEL AISI 304/316 PALLET TRUCK SCALE



Stainless steel pallet truck scale, easy to use, sturdy and suitable for heavy-duty working conditions. Available also in approved version for legal-for-trade use. Manufactured, calibrated and adjusted in Italy by Dini Argeo, with the use of certified sample weights.

Working in cooperation with:

***E H OAKLEY LIMITED***

*Ladymead Farm Unit 4 - HP22 4AN - Aylesbury, Bucks - UNITED KINGDOM  
Tel. 0044 (0) 1296 393133 Fax. 0044 (0) 1296 397070  
adrian@oakleyweigh.co.uk*

**The best solution  
for advanced industrial  
applications**

## WEIGHING FEATURES

- Maximum lifting capacity: 2,000 kg.
- Resolution:
  - > internal use: 0,2 / 0,5 / 1 kg
  - > approved: 0,5 / 1 kg
- Accuracy (weighing of goods on Europallet with distributed load) +/- 1 kg.

## WHY CHOOSE TPWLKI DINI ARGEO

- Stainless steel pallet truck scale, suitable for heavy duty working conditions.
- Available in approved version for legal-for-trade use and with printer for tracking the weighing operations.
- Powered by internal rechargeable battery and about 80 hours of autonomy.
- Built with 4 Dini Argeo load cells, in stainless steel, with IP68 protection.
- Programmable automatic switch-off which lengthens the working autonomy, with battery level indication.
- The large backlit 25 mm LCD display allows an easier reading even in low light conditions.
- Each pallet truck is tested and supplied with a certificate to guarantee the declared precision.

## TECHNICAL FEATURES

- Forks with low profile, only 85 mm.
- Forks dimensions 1150 x 550 x 85 mm.
- Lifting height: 180 mm.
- Weight 135 kg approx.
- High thickness stainless steel AISI 316 supporting structure.
- Steering wheels and loading rollers in nylon.
- Stainless steel AISI 316 Closed fork covers for greater protection of the loading rollers.
- Stainless steel weight indicator AISI 304, with IP65 protection, easy to clean and resistant to harsh and corrosive environments.
- Waterproof and functional 17-key keyboard, with indications for quick recall of the main functions and adjustments.
- Stainless steel AISI 304 lifting pump.
- Battery charger 230Vac 50Hz with EU, AU plug included (charging time approx. 8 hours). Optional UK, US plugs.
- Bi-directional RS232/C port configurable for PC, radio modem or handheld terminal.
- Integrated thermal printer in TPWLKIP and TPWLKIPM versions.
- Operating temperature: -10° / +40°

## THE EASIEST ONE TO CALIBRATE AND REPAIR

- The only one without junction box: the adjustment of each individual cell is done comfortably from the keyboard.
- Spare and wear parts always available and ready for delivery.
- Service centres throughout Europe and the world.

## OTHER VERSIONS AVAILABLE

- Special capacities/resolutions: upon request.
- Other special versions: upon request.

## MAIN FUNCTIONS

- The user can select the operating modes directly using the dedicated key\*:
  - High resolution display x 10
  - Precision weighing with temporary recalibration via a sample weight (for internal factory use)
  - Net/Gross
  - Lb to Kg converter
  - Free conversion factor (for meter and litre counters etc.)
  - Weight totalizer
  - Formulizer
  - +/- controller with quick target and threshold input
  - Percentage weighing
  - Percentage batching with programmable target
  - Piece counter
  - Hold
  - Alibi memory (optional)
- Access to the user menu is gained using the dedicated key\* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.

*\* These quick access keys to the menus can be blocked by configuring a dedicated password.*

## DETAIL 1



## DETAIL 2



Standard printer with dedicated RS232/C bidirectional port (TPWLKIP and TPWLKIPM versions).

## VERSIONS

### Available versions

Codice	Max (kg)	d (kg)	<b>M</b> (kg)
TPWLKI-2	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPWLKIM-2 <b>M</b>	1000 / 2000	--	0,5 / 1
TPWLKIP-2	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPWLKIPM-2 <b>M</b>	1000 / 2000	--	0,5 / 1



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano - Modena - Italy  
Tel. +39.0536 843418

***E H OAKLEY LIMITED***

*Ladymead Farm Unit 4 - HP22 4AN - Aylesbury, Bucks - UNITED KINGDOM*

*Tel. 0044 (0) 1296 393133 Fax. 0044 (0) 1296 397070*

*adrian@oakleyweigh.co.uk*

**SALES AND TECHNICAL ASSISTANCE SERVICE**

*All the specifications and images can be subject to variations and upgrades without prior notice.*