


AELP Pallet Beams with GK Indicator



Speed, Performance, Value - The Right Balance

- Simple user-friendly operation
- Lightweight with handles and wheels for portability
- Precision load cell technology
- Low profile beams to allow easy weighing of pallets using pallet trucks
- Supplied complete with the GK indicator
- 2 beams per set
- Large, clear backlit LCD display
- Selectable digital filtering
- RS-232 uni-directional interface
- Rechargeable battery / mains adapter supplied as standard
- Four load cell construction
- Weighing
- Weight accumulation
- Animal / dynamic weighing



Technical Specifications


Model	AELP-1000 GK	AELP-2000 GK
Maximum capacity	1000kg	2000kg
Readability	200g	500g
Repeatability (S.D.)	200g	500g
Linearity (\pm)	400g	1000g

General Specifications

Typical stabilisation time	2 Sec
Interface	Bi-directional RS-232 output
Power supply	230VAC, 50/60Hz, 115v Optional
Battery	Internal Rechargeable Battery
Display	6 digit LCD with backlight, 9LED bar
Housing	Indicator Housing ABS Plastic
Overall dimensions (wxdxh)	1250x120x85mm
Dimensions notes	Indicator: 240 x 95 x 145 mm
Net weight	50kg

Key Accessories

- AdamDU - Data Collection Program
- In-use Cover
- RS-232 to PC Cable
- ATP Thermal Printer
- Thermal Paper for ATP



Adam Equipment - offices worldwide

www.adamequipment.com