







## Speed, Performance, Value - The Right Balance

- 4 Weighing units (kg, g, lb, oz)
- Colour coded keys
- Hold function
- Full range tare
- Zero Tracking
- Large backlit LCD display
- Kg/ lb/ oz/ lb & oz switchable
- Four load cell construction
- Wall mount bracket
- Large stainless steel platform
- Modern low profile design
- Splashproof to protect from accidental spills
- Simple 4 button operation
- Tare function
- Wheels to allow easy movement
- Rechargeable battery / mains adapter supplied as standard
- RS-232 bi-directional interface
- External calibration
- Rechargeable battery
- Auto sleep / power down function to save battery life
- Low battery indication
- DC Adapter
- Animal / dynamic weighing
- Weighing



## Technical Specifications

Model	CPWplus 35L.	CPWplus 75L.	CPWPlus	CPWPlus	CPWPlus
Maximum capacity	35kg	75kg	<b>150kg</b>	<b>200kg</b>	<b>300kg</b>
Readability	10g	20g	50g	50g	100g
Repeatability (S.D.)	10g	20g	50g	50g	100g
Linearity ( $\pm$ )	20g	40g	100g	100g	200g
Pan size	900 x 600mm				

## General Specifications

Typical stabilisation time	2-3 Sec
Units of measurement	Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Interface	RS-232 bi-directional Interface
Operating temperature	0° 40°C
Calibration	Automatic External with user selectable calibration mass
Display	LCD with minimum 22mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together
Housing	Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform
Dimensions notes	Indicator: 220 x 95 x 43mm (w x d x h)
Net weight	14,4kg

## Key Accessories

- RS-232 to PC Cable
- AdamDU - Data Collection Program
- Rubber non-slip mat for CPWplus L
- RS-232 to USB Interface Cable (must be ordered in conjunction)
- Thermal Paper for ATP
- ATP Thermal Printer



Adam Equipment - offices worldwide

[www.adamequipment.com](http://www.adamequipment.com)