





## Affordability, Durability, Ohaus Quality & Value

The OHAUS VE Series floor platforms and scales are the value solution for your dry or washdown weighing needs in industrial and commercial applications. Their high-quality material and construction are designed to minimize distortion under heavy loads, and ensure years of dependable performance. Available also with corresponding ramps and mounting accessories, the OHAUS VE Series floor platforms and scales offers a unique combination of value, quality and dependability that your company can rely on.

### Standard Features Include:

- 1,500kg and 3,000kg capacities in three platform sizes: 1m x 1m, 1.25m x 1.25m, 1.5m x 1.5m
- Two platform versions with structural bracing that ensures a stiff and solid construction.
- Two rugged OHAUS indicator models:
  - T31P indicator features a high-impact ABS housing with key-holes on the rear cover for wall mounting
- T31XW indicator features a 304 stainless steel IP66 housing
- Four x OIML R60 approved IP67 alloy steel load cells
- Four x load cell mounted feet, self-swiveling ball-in-cup design
- Side access IP65 dust and water immersion protected stainless steel junction box with 5m long cable
- Includes two carbon steel eye bolts that allow easier lifting and positioning of the platform
- Available painted steel and stainless ramps with bottom support ribs that resist bending under heavy loads
- Available second stage verified scale models 1:3000e with OHAUS indicators and fixed-location mounting plates
- OHAUS indicators featuring backlit LCD displays with high-visibility 25mm high digits, five weighing units (kg, g, lb, oz, lb:oz), rechargeable lead acid battery operation (T31P) and piece counting function

# **VE Series** Floor Platforms and Scales

Specifications Platform Models	VE1500S	VE1500R	VE3000R	VE1500L	VE3000L		
Platform Material	Painted carbon steel, raised treaded surface, fixed top plate 5mm thick						
Net Weight	83kg	123kg		170kg			
Platform Models	VE1500SW	VE1500RW	VE3000RW	VE1500LW	VE3000LW		
Platform Material	Stainless steel, sand-blasted flat surface, fixed top plate 5mm thick						
Net Weight	68kg	101kg		134kg			
Platform Size (A x B x min H)	1m x 1m x 9cm	1.25m x 1.25m x 9cm		1.5m x 1.5m x 9cm			
Capacity x Readability	1500kg x 0.5kg	1500kg x 0.5kg	3000kg x 1kg	1500kg x 0.5kg	3000kg x 1kg		
Approval Resolution	1:3000e						
Dperating Temperature / Humidity	-10°C to 40°C / 0% to 95% relative humidity, non-condensing						
Maximum Central Load	125% of rated capacity						
_oad Cell	4 x IP67 alloy steel, shear beam, OIML C3, 5m cable length						
_oad Cell Capacity Emax	1000kg	1000kg	1500kg	1000kg	1500kg		
Dutput Impedance / Excitation /oltage	350 ohm ± 3.5 ohm / 5V~15V, DC/AC						
Feet	4 x self-swiveling ball-in-cup design with rubber bottom, adjustable height						
Junction Box	IP65, 304 stainless steel, with 5m long cable						
Scale Models painted, with T31P indicator)*	VE1500S31P	VE1500R31P	VE3000R31P	VE1500L31P	VE3000L31P		
Scale Models (stainless, with T31XW indicator)*	VE1500S31XW	VE1500R31XW	VE3000R31XW	VE1500L31XW	VE3000L31XW		
ndicators	T31P, ABS plastic / T31XW, 304 stainless steel IP66						
Neighing Units	kg, g, lb, oz, lb:oz						
Display	Backlit LCD, 25 mm high, 6-digit, 7-segment						
nterface	Built-in RS232C, bi-directional						
Power	T31P, AC adapter / T31XW, universal switching power supply						
Battery (T31P only)	Internal rechargeable sealed lead acid battery (100-hour typical operation on full charge)						
Other Features	Piece Counting 1d min APW, Geographical gravity adjustment, Environmental filtering						

\*For 2nd stage EC Type approved Class III models, add "M" at end of scale model name (ex., VE1500S31PM) (will require available foot plate kits in type approved installations)

**Ohaus Number** 


Options	and Ac	ces	SS	ori	es

	enade nam
Wall mount bracket kit, T31P	80251747
Wall mount bracket kit, T31XW	80251748
Ramp kit, VE painted steel, 1m	72198338
Ramp kit, VE painted steel, 1.25m	72198339
Ramp kit, VE painted steel, 1.5m	72198340
Ramp kit, VE-W stainless steel, 1m	72198341
Ramp kit, VE-W stainless steel, 1.25m	72198342
Ramp kit, VE-W stainless steel, 1.5m	72198343
Foot plate kit, VE painted steel	72198344
Foot plate kit, VE-W stainless steel	72198345


#### **Approvals:**

- Safety and EMC: EN60950, EN61326, FCC, CE, CULUS • EC Type Approval:
- T31xx Series Indicator: TC7085 / T5980
- Load Cell: OIML R60 PTB D09-03.19
- Quality: Ohaus quality management system registered to ISO 9001:2000


#### **Structural Features**



#### \*Outline Dimensions (Platform Size)



#### Accessories (Painted Steel & Stainless Steel)



#### www.ohaus.com

